

seaco

BULK POWDER TANKS

SUITABLE FOR ROAD, RAIL AND SEA TRANSPORTATION OF BULK POWDER COMMODITIES
SUCH AS CEMENT, FLY ASH, LIME & PLASTER



FEATURES

- 3 LOADING HATCHES
- COMPRESSED AIR DISCHARGE
- FLUIDISED BED DISCHARGE
- AIR INLET AND CARGO OUTLET QUICK COUPLERS
- INTERNAL TANK SURFACE EPOXY COATED
- ALLOWS BULK TRANSPORTATION OF POWDER

ADVANTAGES

- SAFE AND EFFICIENT LOADING
- MAXIMISES CARGO DISCHARGE RATES
- MINIMISES RESIDUAL CARGO AFTER UNLOADING
- EASY QUICK CONNECTION FOR DISCHARGE
- HIGH CORROSION RESISTANCE
- REDUCED PACKAGING AND HANDLING

BENEFITS

- SAVES TIME AND MAXIMISES LOADED VOLUME
- INCREASES OPERATIONAL EFFICIENCY
- INCREASED EFFICIENCY AND COST SAVINGS
- SAVES TIME AND MONEY
- REDUCED MAINTENANCE AND REPAIR COSTS
- REDUCED COSTS AND WASTAGE

**GLOBAL EXPERTISE
WITH LOCAL KNOWLEDGE**



ANTWERP • BRISBANE • CAPE TOWN • DURBAN • GOTHENBURG • HAMBURG • HOUSTON • LISBON • LONDON • MADRID
 MIAMI • MOSCOW • MUMBAI • PARIS • PERTH • RIODEJANEIRO • SEOUL • SHANGHAI • SINGAPORE • SYDNEY • TAIPEI • TOKYO

A MODERN FLEET OF 45,000 TANKS: BAFFLE TANKS, T11-T14 TANKS, SWAP TANKS, T20/T22 SPECIALISED TANKS, T50 GAS TANKS, BULK POWDER TANKS

CSC AND CLASSIFICATION SOCIETY APPROVED. TANKS IN ACCORDANCE WITH ISO104, TECHNICAL CONDITION AND TESTING METHOD IN ISO1496-3 SERIAL 1- CONTAINER



SEACO HAS A DEDICATED TEAM OF WORLDWIDE SPECIALISTS WHO HAVE CONSTRUCTED ONE OF THE LARGEST LEASING FLEETS OF SPECIALISED CONTAINERS. WITH OUR VAST EXPERIENCE IN THE INDUSTRY, WE WILL FIND THE RIGHT PRODUCT FOR YOUR NEEDS AND TAILOR OUR LEASE AGREEMENTS TO YOUR SPECIFIC REQUIREMENTS.

TECHNICAL SPECIFICATIONS	METRIC
Capacity (Nominal)	28 M ³
Effective Capacity	23.8 M ³
Maximum Gross Weight	34,000 kg
Tare Weight	3,995 kg
Maximum Payload	30,005 kg
Working Pressure	0.2 Mpa
Air Supply	20 M ³ / Min
Diameter of Loading Lid	508 mm
Diameter of Air Inlet	76.2 mm
Diameter of Discharge Pipe	101.6 mm
Discharge Temperature	<50°C
Discharging Height	25m (max)
Discharging Speed to max. 25m height at a horizontal distance of 30m	>0.5 ton/min.
Residual	<60 kg

EXTERNAL DIMENSIONS

Length	6,058 mm
Width	2,502 mm
Height	2,896 mm

FOR DETAILED SPECIFICATIONS OF OUR PRODUCT OFFERING, PLEASE CONTACT YOUR REGIONAL SEACO TANK EXPERT.

AMERICAS

John Lonergan

(+1) 305 597 2129

john.lonergan@seacoglobal.com

EMEIA

Nils Meyer

(+49) 40 8080 3114

nils.meyer@seacoglobal.com

AFRICA: seacoglobal.co.za

NORTH ASIA

Koji Hattori

(+81) 3 4530 9802

koji.hattori@seacoglobal.com

S.EAST ASIA

John Ong

(+65) 6595 1916

john.ong@seacoglobal.com

OCEANIA

Ben Lowry

(+61) 7 3332 8514

ben.lowry@seacoglobal.com

seacoglobal.com.au



an HNA company