

seaco

T20 & T22 SPECIALISED TANKS

A WIDE RANGING FLEET FOR THE INTERMODAL CARRIAGE OF HIGH HAZARDOUS PRODUCTS
AND A VARIETY OF CAPACITIES AND FITTINGS THAT CAN BE CUSTOMISED TO SUIT CUSTOMER REQUIREMENTS

**RIGHT CONTAINER,
RIGHT PLACE, RIGHT TIME**



FEATURES

- 304SS CLADDING
- 12 STEAM HEATING RUNS
- LINED TANKS AND SPECIFIC VALUE COMBINATIONS AVAILABLE
- FITTED WITH "B" TYPE WALKWAY AND OPTION TO FIT HANDRAILS
- NON SLIP STAINLESS STEEL LADDER
- BAFFLES (OPTIONAL)

ADVANTAGES

- FOR DAMAGE AND CORROSION RESISTANCE
- 14 M² LARGER EFFECTIVE HEATING SURFACE PROVIDES EXTRA HEATING CAPACITY WHEN REQUIRED
- TAILORED TO SPECIFIC REQUIREMENTS WHEN NEEDED
- IMPROVED ACCESS AND ADDED SAFETY
- FOR EASY AND SAFE ACCESS TO TOP FITTINGS AND TOP CORNER CASTINGS
- FOR LIQUID SURGE/LOADSHIFT REDUCTION

BENEFITS

- SAVES REPAIR AND MAINTENANCE COSTS
- WIDER OPERATIONAL CAPABILITY
- CONVENIENCE AND FLEXIBILITY TO MEET DEMAND
- ACCORDS WITH ITCO H&S DIRECTIVE
- ACCORDS WITH ITCO H&S DIRECTIVE
- IMPROVED SAFETY



ANTWERP • BRISBANE • CAPE TOWN • DURBAN • GOTHENBURG • HAMBURG • HOUSTON • LISBON • LONDON • MADRID
 MIAMI • MOSCOW • MUMBAI • PARIS • PERTH • RIODEJANEIRO • SEOUL • SHANGHAI • SINGAPORE • SYDNEY • TAIPEI • TOKYO

A MODERN FLEET OF 45,000 TANKS:

BAFFLE TANKS, T11-T14 TANKS,

SWAP TANKS,

T20/T22 SPECIALISED TANKS,

T50 GAS TANKS

TANKS IN ACCORDANCE WITH UN PORTABLE TANK T20, IMDG, RID/ADR, CSC, TIR, TC IMPACT APPROVED, US-DOT, UIC, ISO, ASME VIII DIV.1 (U STAMP), CFR 49

- ✓ Tailored Leasing Solutions
- ✓ Equipment available for specific periods of time at fixed terms to meet peak or seasonal demands

	Metric	Imperial	Metric	Imperial	Metric	Imperial
Capacity	14,500 ltr	3,830 US Gallons	17,500 ltr	4,623 US Gallons	21,000 ltr	5,547 US Gallons
Maximum Gross Weight	36,000 kg	79,366 lb	36,000 kg	79,366 lb	36,000 kg	79,366 lb
Tare Weight	3,860 kg	8,509 lb	4,700 kg	10,362 lb	4,650 kg	10,251 lb
Maximum Allowable Working Pressure (MAWP)	6.67 bar	97 psi	6.67 bar	97 psi	6.67 bar	97 psi
Test Pressure	10 bar	145 psi	10 bar	145 psi	10 bar	145 psi
Steam Working Pressure	4.0 bar	58 psi	4.0 bar	58 psi	4.0 bar	58 psi
Ambient Temperature Range	-40°C to +65°C	-40°F to +149°F	-40°C to +65°C	-40°F to +149°F	-40°C to +65°C	-40°F to +149°F
Maximum Cargo Temperature	+130°C	+266°F	+130°C	+266°F	+130°C	+266°F
Shell and Head Material	SANS 50028-7 (2005): 1.4402		SANS 50028-7 (2005): 1.4402		SANS 50028-7: 1.4402/1.4404	



SEACO HAS A DEDICATED TEAM OF WORLDWIDE SPECIALISTS WHO HAVE CONSTRUCTED ONE OF THE LARGEST LEASING FLEETS OF SPECIALISED CONTAINERS. WITH OUR VAST EXPERIENCE IN THE INDUSTRY, WE WILL FIND THE RIGHT PRODUCT FOR YOUR NEEDS AND TAILOR OUR LEASE AGREEMENTS TO YOUR SPECIFIC REQUIREMENTS.

FOR DETAILED SPECIFICATIONS OF OUR PRODUCT OFFERING, PLEASE CONTACT YOUR REGIONAL SEACO TANK EXPERT.

AMERICAS

John Lonergan

(+1) 305 597 2129

john.lonergan@seacoglobal.com

EMEIA

Nils Meyer

(+49) 40 8080 3114

nils.meyer@seacoglobal.com

AFRICA: seacoglobal.co.za

NORTH ASIA

Koji Hattori

(+81) 3 4530 9802

koji.hattori@seacoglobal.com

S.EAST ASIA

John Ong

(+65) 6595 1916

john.ong@seacoglobal.com

OCEANIA

Ben Lowry

(+61) 7 3332 8514

ben.lowry@seacoglobal.com

seacoglobal.com.au



an **HNA** company